



## NIPPON MULTI-PURPOSE JOINT COMPOUND

### **Product Description:**

Nippon Multi-purpose Joint Compound is specially formulated as ready to use skimcoat material to smoothen uneven plastering wall, painted surfaces and gypsum to give a smooth and excellent finishing. It has good workability and sanding property that is ideal for patching cracks and drywall joints.

It also provides good compatibility and adhesion with wide range of Nippon Paint interior paints and wall sealer.

### **Recommended Uses:**

Nippon Multi-purpose Joint Compound is recommended for interior wall surface and ceiling. It is recommended to apply 1 coat of Nippon Hi-Bond Wall Sealer/ Nippon Eco-bond first before top coat to provide better performance and appearance of the top coat.

### **Composition:**

<b>Pigments</b>	: Mineral Extender
<b>Binder</b>	: Vinyl Acetate Copolymer Emulsion
<b>Thinner</b>	: Water
<b>Specific Gravity</b>	: 1.60 – 1.80

### **Properties:**

**Colour and Texture** : White and Flat

### **Drying Time (30°C)**

Touch Dry	: 15 minutes
Hard Dry	: 1 hour
Sanding	: 3 hours (No. 300 - 600 sanding paper)

**Theoretical Coverage at Recommended Dry Film Thickness** : Depending on surface condition.

### **Application Methods:**

**1) Spatula, Trowel**

**Clean Up** : Clean up equipment with water immediately after use.

**Surface Preparation:**

Remove dust, grease, oil and other foreign matters of surface.

**Standard Packing**

: 5 kg, 28 kg

**Safety, Health and Environmental Information:**

Keep container tightly closed and keep out of reach of children or away from food and drink.  
Ensure good ventilation during application and drying.  
When applying paint, it is advisable to wear eye protection.  
In case of contact with eye, rinse with plenty of water immediately and seek medical advice.  
Remove splashes from skin by using soap or water.  
Paint must always be stored in a cool place.  
When transporting paint, care must be taken. Always keep container in a secure upright position.  
Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given data without prior notice.